



xylem



Environmental
Monitoring



YSI 9800 Photometer

Flexible photometer for the lab or field



9800 Photometer

Simple. Convenient. Accurate.

The **YSI 9800 Photometer** streamlines water quality analysis through easy, step-by-step instructions for dozens of parameters on a large touchscreen display. A portable, waterproof design makes this the ideal instrument for any water quality application both in the field and lab. The 9800 uses the same reagents as previous photometer models and all reagents are safe and easy to use.



Benefits of the 9800 Photometer



Quick and accurate testing

Simple on-screen instructions guide you through dozens of test options



Multiparameter sampling

Get more comprehensive data with over 25 parameters on a single instrument



Touch screen interface

Easily view testing options, settings, and results even when wearing gloves



Rugged design

Field-ready housing is impact tested, waterproof, and scratch resistant



Data management

Test results are saved automatically with easy data retrieval



Easy-to-use reagents

Reagents are safe to use regardless of form



Select Test

Select from a list of all Tests or Favorite Tests



Users

Add up to 50 user names for increased traceability



Check Standards

The 9800 can be verified with a set of standards



Labels

Use labels to tag data for later filtering



Test Log

View logged data and filter to view subsets



System Settings

Set up and customize your 9800 Photometer

Photometry made simple

The **9800 Photometer** uses an advanced, innovative optical design that allows for accurate and reliable testing both in the lab or field. Perform tests with step-by-step instructions, view and export data, save test logs, and more from the large touchscreen. It's capable of running multiple tests using industry standard methods for over 25 different parameters for a variety of water quality applications.

9800 Photometer Specifications

Instrument type	Multiparameter photometer
Wavelengths	430 nm, 465 nm, 530 nm, 575 nm, 620 nm
Accuracy	± 1%T (transmission)
Display	Large, Color LCD
User interface	Touch screen with walkthrough text instructions
Dimensions	Width: 211 mm (8.3 in) Length: 195 mm (7.7 in) Height: 52 mm (2.0 in)
Weight	0.85 kg (1.87 lbs)
IP rating	IP-67
Power supply	6x AA Batteries or through USB
Connectivity	Connect to PC via USB cable
Memory capacity	1,000 data sets
Battery life	5,000 tests on one set of batteries
Languages	English, French, Spanish, and Chinese (Simplified)
Certifications	EN61326, EN61010, IP67, and EN60068-2-78

Parameters

Alkalinity, Total	Iron MR
Aluminum	Iron HR
Ammonia	Magnesium
Bromine	Manganese
Calcium Hardness	Nickel
Chlorine, Combined	Nitrate
Chlorine, Free	Nitrite
Chlorine, Total	Ozone
Copper	pH- Phenol Red
Cyanuric Acid	Phosphate LR
Fluoride	Potassium
Hardness, Total	Sulfate
Iron LR	Turbidity



Ordering information

9800 Photometer Test Kits

Test Kits	Range (mg/L)	Starter (50)	Replace (250)	Sea Water Use ⁴
Alkalinity, Total (Alkaphot)	0-500 (CaCO ₃)	YPM188	YAP188	Suitable
Aluminum	0-0.5	N/A	YAP166	
Ammonia	0-1.0 (N)	YPM152	YAP152	Suitable with use of Ammonia Conditioning Reagent YAT1707
Bromine	0-10.0	N/A	YAP060	
Calcium Hardness (Calcicol)	0-500 (CaCO ₃)	YPM252	YAP252	Suitable under certain circumstances**
Chlorine DPD, Free	0-5.0	N/A	YAP011	
Chlorine DPD - Free, Mono- and Dichloramine; requires (YAP011)	0-5.0	N/A	YAP021	
Chlorine DPD - Free, Combined and Total	0-5.0	YPM031	N/A	
Color (includes turbidity)	10-500 CU	YPM269	N/A	
Copper (Coppercol) (free, combined, total)	0-5.0	YPM186	YAP186	
Copper (free)	0.03-5.0	N/A	YAP187	
Cyanuric Acid	0-200	N/A	YAP087	
Fluoride	0-1.5	YPM179	YAP179*	
Hardness (Hardicol)	10-500 (CaCO ₃)	YPM254	YAP254	
Iron LR ¹	0-1.0	YPM155	N/A	Suitable
Iron MR ³	0-5.0	YPM292	YAP292	
Iron HR ²	0-10	N/A	YAP156	
Magnesium (Magnecol)	0-100	YPM193	YAP193	Not suitable
Manganese	0-0.03	YPM173	YAP173	
Nickel	0-10	N/A	YAP284*	
Nitrate	0-20 (N)	YPM163	YAP163*	Suitable with filtration of samples
Nitrite (N)	0-0.5 (N)	YPM109	YAP109	Suitable with filtration of samples
Nitrite (NaNO ₂)	0-1500 (NaNO ₂)	YPM260	YAP260	Suitable with filtration of samples
Ozone	0-3.0	N/A	YAP056	
pH - Phenol Red	6.8-8.4	YPM130	YAP130	
Phosphate LR ¹	0-4.0	YPM177	YAP177*	Suitable
Potassium	0-12	YPM189	YAP189	
Sulfate	0-200	YPM154	YAP154	

* Includes 200 tests **Filtration of sea water samples required. Calcium salt instrument calibration needed for sample concentrations of over 3,500 mg/L salt

¹ LR denotes low range.

² HR denotes high range.

³ MR denotes mid range

⁴Sea Water Use denotes tests that have been evaluated for sea water testing. Blank notes indicate the test has not been verified



YSI Incorporated
1725 Brannum Lane
Yellow Springs, OH 45387

Tel +1 937.767.7241
Email info@ysi.com
YSI.com

